



NOTES:
 1) MATERIAL:
 HOUSING: HI-TEMP. PLASIC UL 94V-0
 CONTACT: COPPER ALLOY
 SHELL: STAINLESS STEEL
 2) FINISH:
 CONTACT: GOLD FLASH PLATED ON CONTACT AREA;
 GOLD FLASH PLATED ON SOLDER TAILS,

■ CIRCUT TRACE KEEP OUT AREA
 ■ SMT SOLDER AREA
 THERE SHOULD NOT BE ANY CIRCUITRIES
 IN THE LAYOUT SPACE OF THE PRODUCTS.
 RECOMMENDED PCB LAYOUT
 GENERAL TOLERANCE ±0.05

SWITCH CONNECTOR

SIM pin Assignment	
PIN#	Name
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O

						DSND		DATE		SCALE: N/A	MODEL TYPE: SIM CARD CONN	
Δ X						DWN		DATE		VIEW:	PART NO.:	
Δ X						CHKD		DATE		UNIT: mm	DWG NO.:	
Δ X						APPD		DATE		SIZE: A4	XKSIM-114	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT 1.0g	SHEET 1/1	REVISION A0
REVISIONS												
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn												