



Specification:  
 \*Electrical Characteristics:  
 Current Rating;1.5A.  
 Withstanding Voltage:AC500V r.m.s.  
 Insulation Resistance:1000Megohms  
 Minimum at DC 500V  
 Contact Resistance:100Miliohms  
 Maximum.  
 \*Mechanical Characteristics:  
 Mating Cyeles:5000 Insertions.

PART NUMBER INFORMATION

Connector terminal NO.	Pin NO.
Pin 1	VCC:PWR signal and GND
Pin 2	RST:Reset signal
Pin 3	CLK:Clocking signal
Pin 4	RESERVED
Pin 5	GND:PWR signal and GND
Pin 6	VPP:Porgramming Voltage
Pin 7	I/O:Serial date input/output
Pin 8	RESERVED

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: SIM CARD CONN
△X					ANGLAR ±5°	DWN	DATE	VIEW:	PART NO.:
△X					L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm	DWG NO.:
△X					4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	<b>XKSIM-220</b>
					16 < L ≤ 63 ±0.4				WEIGHT 1.0g
					L > 63 ±0.5				SHEET 1/1
									REVISION A0
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn						<b>XKB INDUSTRIAL PRECISION CO.,LIMITED</b>			