



Pin No.	NAME	TYPE
1	DAT 2	I/O/PP
2	CD/DAT 3	I/O/PP
3	CMD	PP
4	VDD	S
5	CLK	I
6	VSS	S
7	DAT0	I/O/PP
8	DAT1	I/O/PP

RECOMMENDED P.C.B LAYOUT(TOP VIEW)
GENERAL TOLERANCE ±0.05

NOTE:

- ELECTRICAL CHARACTERISTICS
 - CONTACT RESISTANCE: 50 milliohms MAX.
 - INSULATION RESISTANCE: 1,000 Megohms MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
- MECHANICAL CHARACTERISTICS
 - RETENTION FORCE: MIN.100gf/PIN
 - RoHS 2002/95/EC COMPLIANT.
- RESISTANCE TO REFLOW SOLDERING HEAT: 260°C Max

ITEM	NAME	Q'TY	MATERIAL	FINISHED	NOTE
3	TERMINAL	10	C268DH	Au PLATING	CONTACT AREA: Au 15u",G/F ON SOLDER-TAIL
2	SHIELD	1	C2680H	Ni PLATING	
1	HOUSING	1	LCP		UL 94V-0

SWITCH CONNECTOR

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: TF CARD CONN		
ΔX					ANGLAR ±5°	DWN	DATE	VIEW:	PART NO.:		
ΔX					L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm	DWG NO.:		
ΔX					4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	XKTF-005		
					16 < L ≤ 63 ±0.4	XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT	SHEET	REVISION
					L > 63 ±0.5				1.0g	1/1	A0